





Grade 80 Clevis Grab Hook

Clevis grab hook with support lug enables easy connection to lifting slings and provides back hooking for adjustable chain slings.

Applications

- Use with Grade 80 lifting components
- · Lifting with chains and synthetic slings
- · Clevis connection for direct attachment to chain

Material



Grade 80

Finish



Powder Coat



Features

- · Conforms to AS 3776
- 100% magnaflux crack detection
- Ability to shorten lengths of chain
- Can be used for back hooking




Part	QFind	Size	WLL	BL	Dimensions			
		(mm)	(tonne)	(tonne)	A (mm)	H (mm)	E (mm)	L (mm)
ULHK08PGC-06	HGC6	6	1.12	4.48	8.00	17.7	8.0	77.3
ULHK08PGC-08	HGC8	8	2.00	8.00	9.50	18.5	10.5	89.0
ULHK08PGC-10	HGC10	10	3.15	42.60	12.50	29.0	13.0	126.0
ULHK08PGC-13	HGC13	13	5.30	21.20	15.00	42.5	16.5	163.5
ULHK08PGC-16	HGC16	16	8.00	32.00	18.50	45.5	19.0	183.5
ULHK08PGC-20	HGC20	20	12.50	50.00	23.00	56.0	24.0	219.0
ULHK08PGC-22	HGC22	22	15.00	60.00	27.00	68.5	27.0	254.0
ULHK08PGC-26	HGC26	26	21.20	84.80	30.00	77.0	30.0	309.0



MARKINGS:

- CE (European Conformity)
- WLL (Working Load Limit)
- Trace Code (linked to certificate online)
- Manufacturer's mark





Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document.

